# True Ice Series: Modular Cubed Ice Maker TCIM-522





TCIM-522-HA1-A *TIB-422* 

# **CUBE SIZES**







# FEATURES & BENEFITS

# Produces up to 560 lbs. of ice per 24 hours

- Environmentally friendly R290 refrigeration system for optimum ice production and energy efficiency
- 30% below DOE 2018
- 20% below Energy Star

# **Superior Sanitation**

- TrueZone\* protection to purify surrounding air in bin and food zone
- TrueGuard Antimicrobial embedded in every plastic piece including bin liners
- Food zone pieces easily removed without tools
- Simple 1-touch cleaning
- Easily removable air filter with RCU technology

# **Advanced Control with Touch Screen**

- 4.3" front display largest in the industry
- Simple touch operation
- Advanced diagnostics which allows for predictive and proactive measures
- Built-in alarms & push notifications
- Programmable ice production
- Time-of-Flight<sup>™</sup> ice sensor eliminates the need for bin thermostats

# **Remote Monitoring Capabilities**

- · Remote monitoring with easy back end data access
- · Location based performance enhancement
- · Remote shut off

Commercial Ice Maker Warranty					
Ice Maker	3 YEARS parts and labor				
Compressor	<b>5 YEARS</b> parts				
Evaporator	<b>5 YEARS</b> parts and labor				

<sup>\*</sup>TrueZone device sold as optional accessory

True Mfg. – Ice Makers TCIM-522-HA1-A Item#: Ice Maker

# True Ice Series: Modular Cubed Ice Maker TCIM-522



# ADDITIONAL FEATURES

# **Evaporator Plate:**

- High performance copper
- · No harvest assist necessary
- TrueNcap<sub>su</sub>L<sub>8</sub> Sanitary evaporator fully insulated & sealed for efficiency and cleanliness

#### **Construction:**


 TrueTech aluminum front and sides, all plastic interior and single piece case for both 22" & 30" units

# **Refrigeration System:**


- · Environmentally friendly R290 Refrigerant
- High & low pressure transducers for gauge-free servicing
- Micro channel condenser for superior efficiency
- Wide operating range: 35°F to 110°F ambient
- · Ultra quiet fan operation

# AIR COOLED

Please note: air-cooled units require 6" (15.24mm) clearance for air intake and exhaust on the left, right, and back sides.



# **PLAN VIEW**



SPECIFICATIONS											
Model	Condenser Type	Refrigerant	Cube Size	Crated Weight (Ibs)	@ 70°F air/50°F water	@ 90°F air/70°F water			Peak Heat of	Voltage	Min Circuit
					Ice Production per 24hr	Ice Production per 24hr	Potable Water Consumption	Electrical Consumption	Rejection	voitage	Ampacity
TCIM-522-HA1-A	Air	R290	Half	200	640 lbs (290 kg)	580 lbs (227 kg)	14.2 gal/100lb	4.15 kWh/100lb	8500 BTU/hr	115/60/1	15
TCIM-522-FA1-A	Air	R290	Full	200	640 lbs (290 kg)	*	*	*	8500 BTU/hr	115/60/1	15
TCIM-522-LA1-A	Air	R290	Large	200	640 lbs (290 kg)	*	*	*	8500 BTU/hr	115/60/1	15

OPTIC	NS & ACCESS	OPERATING REQUIREMENTS			
	Water Filte		Minimum	Maximum	
Filter System	R	eplacement Cartridge	Ambient Air Temp:	35°F (1.7°C)	110°F (43.3°C)
P/N 855953		P/N 855884	Water Temp:	35°F (1.7°C)	100°F (37.7°C)
C	CONNECTIONS	Water Pressure:	20 psi (138 kPa)	100 psi (689 kPa)	
Potable wa	ater in:	1/2" Female NPT	DIMENSIONS		
Water o	out:	3/4" Female NPT	W x D x H (in.)	30 x 24 x 22	

7/8"

Hole for electrical connections:



 $W \times D \times H (mm)$ 





767 x 627 x 564



 $<sup>\</sup>ensuremath{^*}$  Waiting on Energy Star Listing.

# True Ice Series: Slope Front Storage Bins

HIGH CAPACITY COMMERCIAL EQUIPMENT THE FUTURE OF THE ICE INDUSTRY







**TIB-422** 

**TIB-530** 

# FEATURES & BENEFITS

- Tru-tech aluminum exterior with heavy duty plastic lid and frame
- All plastic interior plus 100% antimicrobial plastic liner
- Fully insulated with environmentally friendly high-density polyurethane foam
- Slow Close Lid/Hinge design
- · Removable Ice Baffle
- Magnascoop® included for easy ice scoop storage


Model	Capacity	Dimensions	Crated Weight (lbs)
TIB-422	320 lbs	22" x 34" x 50" 559 x 864 x 1270 mm	140
TIB-530	450 lbs	30" x 34" x 50" 762 x 864 x 1270 mm	175

# **BIN ACCESSORIES**

- 3" Adjustable legs
- Adapter top for 22" machine head on 30" bin

#### PLAN VIEWS

# **TIB-422**



# **TIB-530**

